



HIGHNESS™

One of a kind

8.4" OPEN FRAME DISPLAY

FM084XG001



Update Date
12th Jun 2020

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS SOLELY OWNED BY 'HIGHNESS MICROELECTRONICS LTD'. ANY UNAUTHORISED COPY OR PRINTING OR PUBLISHING OF INFORMATION IN THIS DOCUMENT IN PART OR IN COMPLETE IS RESTRICTED.

HIGHNESS MICROELECTRONICS LTD.

URL: www.highnessmicro.com, Email: sales@highnessmicro.com

1. Technical Specification

Screen Size	8.4" diagonal	
Active Area (H x V)	170.496 x 127.872 mm	
Resolution	1024 x 768	
Aspect Ratio	4:3	
Pixel Pitch (H x V)	0.1665 x 0.1665 mm	
Color	16.7M	
Viewing Angle	88°/88°/88°/88°	
Luminance	400 cd/m ² (Standard Model)	
	500~900 cd/m ² (High Brightness Model)	
Contrast	600:1	
Response Time	50ms	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
Power Input	12V DC	
Power Consumption	20 Watt	
Backlight Type	LED	
Backlight Life	70,000 hours	
Enclosure	Mild Steel / Aluminum	
Mounting	Front Mounting	
	Back Mounting, VESA mount (Optional)	

2. Touch Screens (Optional)

2.1 Projected Capacitive Touchscreen

Touch Screen Type	Projected Capacitive
Interface	USB / I2C / UART
Input Method	Finger
Transparency	$\geq 80\%$ ($\pm 3\%$)
Haze	$< 3\%$
Surface Type	Antiglare
Operating Force	10-80 g
Durability	3,000,000 touch at a single point
Hardness	$> 3H$
Capacitance	$< 5\text{ Nf}$
Supported OS	Windows, Linux & Android

2.2 Resistive Analog Touchscreen

Touch Screen Type	4/5 Wire Resistive
Interface	USB
Input Method	Stylus or Finger
Transparency	$\geq 85\%$ ($\pm 3\%$)
Haze	$< 3\%$
Surface Type	Antiglare
Operating Force	70-100 g
Durability	1,000,000 touch at a single point
Hardness	$> 3H$
Supported OS	Windows & Linux

3. Enhancement Solutions (Optional)

3.1. Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating

Particulars	Details
Reflection	0.57%
Transparency	92%
Haze	15%
Surface Hardness	3H

3.2. Surface Hardness Coating

Particulars	Details
Hardness	Upto 9H
Transparency	91.3%
Haze	0.2%
Water Resistance	60°C, 90% RH
Heat Resistance	140°C

3.3. Optical Bonding

Particulars	Details
Structure	Glass + Glass (Soda Lime Glass + TFT-LCD Module or Touch Screen + TFT-LCD Module)
Temperature	-40 to +85°C
Humidity	0 to 95% RH
Transparency	91%
UV Resistance	UVA 340nm

Model Numbers / Ordering Information

Model No.	Particulars	Details
FM084XG001	Base Model	-
FM084XG001-xx	Brightness	High Brightness
FM084XG001-xx-A	Input Interface	HDMI
FM084XG001-xx-B		HDMI, DVI & VGA Input
FM084XG001-xx-y-PT	Touch Screens	Projected Capacitive
FM084XG001-xx-y-4R		4 Wire Resistive Analog
FM084XG001-xx-y-5R		5 Wire Resistive Analog
FM084XG001-xx-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
FM084XG001-xx-y-zz-HF		Surface Hardness Coating
FM084XG001-xx-y-zz-OB		Optical Bonding

(Manufacturer reserves the sole right to change the specifications without prior notice)
(Touch screen will reduce the original luminance of the LCD display)