



HIGHNESS™

One of a kind

17" Industrial Grade Display

ID170SX001



Release Date
22nd May 2020

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS SOLELY OWNED BY 'HIGHNESS MICROELECTRONICS PVT. LTD.' MUMBAI.
ANY UNAUTHORISED COPY OR PRINTING OR PUBLISHING OF INFORMATION IN THIS DOCUMENT IN PART OR IN COMPLETE IS RESTRICTED.

HIGHNESS MICROELECTRONICS PVT. LTD

URL: www.highnessmicro.com, Email: sales@highnessmicro.com

1. Technical Specification

Screen Size	17" diagonal	
Active Area (H x V)	337.920 x 270.336 mm	
Resolution	1280 x 1024	
Aspect Ratio	4:3	
Pixel Pitch (H x V)	0.264 x 0.264 mm	
Color	16.2M	
Viewing Angle	85°/85°/80°/80°	
Luminance	350 cd/m ² (Standard Model)	
	500~900 cd/m ² (High Brightness Model)	
Contrast	1000:1	
Response Time	9ms	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	12V DC	
Power Consumption	18 Watt	
Backlight Type	LED	
Backlight Life	30,000 hours	
Enclosure	Mild Steel / Aluminum	
Mounting	VESA standard / Wall Mount	

2. Touch Screens (Optional)

2.1 Projected Capacitive Touchscreen

Touch Screen Type	Projected Capacitive
Interface	USB / I2C / UART
Input Method	Finger
Transparency	≥ 80% (± 3%)
Haze	< 3%
Surface Type	Antiglare
Operating Force	10-80 g
Durability	3,000,000 touch at a single point
Hardness	> 3H
Capacitance	< 5 Nf
Supported OS	Windows, Linux & Android

2.2 Resistive Analog Touchscreen

Touch Screen Type	4/5 Wire Resistive
Interface	USB
Input Method	Stylus or Finger
Transparency	≥ 85% (± 3%)
Haze	< 3%
Surface Type	Antiglare
Operating Force	70-100 g
Durability	1,000,000 touch at a single point
Hardness	> 3H
Supported OS	Windows & Linux

3. Enhancement Solutions (Optional)

3.1. Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating

Particulars	Details
Reflection	0.57%
Transparency	92%
Haze	15%
Surface Hardness	3H

3.2. Surface Hardness Coating

Particulars	Details
Hardness	Upto 9H
Transparency	91.3%
Haze	0.2%
Water Resistance	60°C, 90% RH
Heat Resistance	140°C

3.3. Optical Bonding

Particulars	Details
Structure	Glass + Glass (Soda Lime Glass + TFT-LCD Module or Touch Screen + TFT-LCD Module)
Temperature	-40 to +85°C
Humidity	0 to 95% RH
Transparency	91%
UV Resistance	UVA 340nm

Model Numbers / Ordering Information

Model No.	Particulars	Details
ID170SX001	Base Model	-
ID170SX001-xx	Brightness	High Brightness
ID170SX001-xx -A	Input Interface	HDMI
ID170SX001-xx-B		HDMI, DVI & VGA Input
ID170SX001-xx-C		DVI, HDMI, S-Video, Composite Video & VGA
ID170SX001-xx-y-PT	Touch Screens	Projected Capacitive
ID170SX001-xx-y-RT		4 Wire Resistive Analog
ID170SX001-xx-y-5RT		5 Wire Resistive Analog
ID170SX001-xx-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID170SX001-xx-y-zz-HF		Surface Hardness Coating
ID170SX001-xx-y-zz-OB		Optical Bonding

(Manufacturer reserves the sole right to change the specifications without prior notice)
(Touch screen will reduce the original luminance of the LCD display)