



HIGHNESS™

One of a kind

32" Industrial Grade Display

ID320UH001



Release Date
25th May 2020

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS SOLELY OWNED BY 'HIGHNESS MICROELECTRONICS PVT. LTD.' MUMBAI.
ANY UNAUTHORISED COPY OR PRINTING OR PUBLISHING OF INFORMATION IN THIS DOCUMENT IN PART OR IN COMPLETE IS RESTRICTED.

HIGHNESS MICROELECTRONICS PVT. LTD

URL: www.highnessmicro.com, Email: sales@highnessmicro.com

1. Technical Specification

Screen Size	32" diagonal
Active Area (H x V)	708.48 x 398.52 mm
Resolution	3840 x 2160
Aspect Ratio	16:9
Pixel Pitch (H x V)	184.5 x 184.5 μm
Color	1.07B
Viewing Angle	89°/89°/89°/89°
Luminance	350 cd/m ² (Standard Model) 500~900 cd/m ² (High Brightness Model)
Contrast	1000:1
Response Time	12ms
Operating Temperature	-20° to +70° C
Storage Temperature	-20° to +70° C
Video Inputs Signals	HDMI, DVI & DP
Video Output Signals	DP
Power Input	AC 240V
Power Consumption	60 Watt
Backlight Type	LED
Backlight Life	30,000 hours
Enclosure	Mild Steel / Aluminum
Mounting	VESA standard / Wall Mount

2. Touch Screens (Optional)

2.1 Projected Capacitive Touchscreen

Touch Screen Type	Projected Capacitive
Interface	USB / I2C / UART
Input Method	Finger
Transparency	≥ 80% (± 3%)
Haze	< 3%
Surface Type	Antiglare
Operating Force	10-80 g
Durability	3,000,000 touch at a single point
Hardness	> 3H
Capacitance	< 5 Nf
Supported OS	Windows, Linux & Android

2.2 Resistive Analog Touchscreen

Touch Screen Type	4/5 Wire Resistive
Interface	USB
Input Method	Stylus or Finger
Transparency	≥ 85% (± 3%)
Haze	< 3%
Surface Type	Antiglare
Operating Force	70-100 g
Durability	1,000,000 touch at a single point
Hardness	> 3H
Supported OS	Windows & Linux

3. Enhancement Solutions (Optional)

3.1. Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating

Particulars	Details
Reflection	0.57%
Transparency	92%
Haze	15%
Surface Hardness	3H

3.2. Surface Hardness Coating

Particulars	Details
Hardness	Upto 9H
Transparency	91.3%
Haze	0.2%
Water Resistance	60°C, 90% RH
Heat Resistance	140°C

3.3. Optical Bonding

Particulars	Details
Structure	Glass + Glass (Soda Lime Glass + TFT-LCD Module or Touch Screen + TFT-LCD Module)
Temperature	-40 to +85°C
Humidity	0 to 95% RH
Transparency	91%
UV Resistance	UVA 340nm

Model Numbers / Ordering Information

Model No.	Particulars	Details
ID320UH001	Base Model	-
ID320UH001-xx	Brightness	High Brightness
ID320UH001-xx-PT	Touch Screens	Projected Capacitive
ID320UH001-xx-4R		4 Wire Resistive Analog
ID320UH001-xx-5R		5 Wire Resistive Analog
ID320UH001-xx-yy-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID320UH001-xx-yy-HF		Surface Hardness Coating
ID320UH001-xx-yy-OB		Optical Bonding

(Manufacturer reserves the sole right to change the specifications without prior notice)
(Touch screen will reduce the original luminance of the LCD display)