



HIGHNESSTM

One of a kind

15.6" Industrial Grade Panel Mount Display

PM156FH001-HB



Update Date
29th Jun 2020

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS SOLELY OWNED BY 'HIGHNESS MICROELECTRONICS LTD'. ANY UNAUTHORISED COPY OR PRINTING OR PUBLISHING OF INFORMATION IN THIS DOCUMENT IN PART OR IN COMPLETE IS RESTRICTED.

HIGHNESS MICROELECTRONICS LTD.

URL: www.highnessmicro.com, Email: sales@highnessmicro.com

1. Technical Specification

Screen Size	15.6" diagonal	
Active Area (H x V)	344.16 x 193.59 mm	
Resolution	1920 x 1080	
Aspect Ratio	16:9	
Pixel Pitch (H x V)	0.17925 x 0.17925 mm	
Color	16.7M	
Viewing Angle	80°/80°/75°/75°	
Luminance	500 cd/m ² (Standard Model)	
	500~900 cd/m ² (High Brightness Model)	
Contrast	600:1	
Response Time	13ms	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	12V DC	
Power Consumption	28 Watt	
Backlight Type	LED	
Backlight Life	50,000 hours	
Handle	2x Industrial Grade Rugged Handle (Optional)	
Enclosure	Mild Steel / Aluminum	
Mounting	Front Mounting	
	Back Mounting, VESA mount (Optional)	

2. Touch Screens (Optional)

2.1 Projected Capacitive Touchscreen

Touch Screen Type	Projected Capacitive
Interface	USB / I2C / UART
Input Method	Finger
Transparency	$\geq 80\%$ ($\pm 3\%$)
Haze	$< 3\%$
Surface Type	Antiglare
Operating Force	10-80 g
Durability	3,000,000 Touch at a Single Point
Hardness	$> 3H$
Capacitance	$< 5\text{ Nf}$
Supported OS	Windows, Linux & Android

2.2 Resistive Analog Touchscreen

Touch Screen Type	4/5 Wire Resistive
Interface	USB
Input Method	Stylus or Finger
Transparency	$\geq 85\%$ ($\pm 3\%$)
Haze	$< 3\%$
Surface Type	Antiglare
Operating Force	70-100 g
Durability	1,000,000 Touch at a Single Point
Hardness	$> 3H$
Supported OS	Windows & Linux

3. Enhancement Solutions (Optional)

3.1. Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating

Particulars	Details
Reflection	0.57%
Transparency	92%
Haze	15%
Surface Hardness	3H

3.2. Surface Hardness Coating

Particulars	Details
Hardness	Upto 9H
Transparency	91.3%
Haze	0.2%
Water Resistance	60°C, 90% RH
Heat Resistance	140°C

3.3. Optical Bonding

Particulars	Details
Structure	Glass + Glass (Soda Lime Glass + TFT-LCD Module or Touch Screen + TFT-LCD Module)
Temperature	-40 to +85°C
Humidity	0 to 95% RH
Transparency	91%
UV Resistance	UVA 340nm

3.4. EMI-MESH

Item		Value
Mesh Composition Base Material/ (Plated Deposit)		Copper
Openings/ inch		82
Wire Diameter		8µm
Surface Resistance		< 0.15Ω/m ²
H Field 1MHz		89
E 10 MHz		90
Plane Wave	100 MHz	84
	400 MHz	77
	1 GHz	62
	10 GHz	42

Model Numbers / Ordering Information

Model No.	Particulars	Details
PM156FH001-HB	Brightness	High Brightness
PM156FH001-HB-A	Input Interface	HDMI
PM156FH001-HB-B		HDMI, DVI & VGA Input
PM156FH001-HB-C		DVI, HDMI, S-Video, Composite Video & VGA
PM156FH001-HB-y-PT	Touch Screens	Projected Capacitive
PM156FH001-HB-y-RT		4 Wire Resistive Analog
PM156FH001-HB-y-5RT		5 Wire Resistive Analog
PM156FH001-HB-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
PM156FH001-HB-y-zz-HF		Surface Hardness Coating
PM156FH001-HB-y-zz-OB		Optical Bonding
PM156FH001-HB-y-zz-##-E		EMI-MESH

 (Manufacturer reserves the sole right to change the specifications without prior notice)
 (Touch screen will reduce the original luminance of the LCD display)