


10.4" OPEN FRAME DISPLAY

FM104SV001



Model Numbers / Ordering Information

Model No.	Particulars	Details
FM104SV001	Base Model	-
FM104SV001-xx	Brightness	High Brightness
FM104SV001-xx-A	Input Interface	HDMI
FM104SV001-xx-B		HDMI, DVI & VGA Input
FM104SV001-xx-y-PT	Touch Screens	Projected Capacitive
FM104SV001-xx-y-RT		4 Wire Resistive Analog
FM104SV001-xx-y-5RT		5 Wire Resistive Analog
FM104SV001-xx-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
FM104SV001-xx-y-zz-HF		Surface Hardness Coating
FM104SV001-xx-y-zz-OB		Optical Bonding



Technical Specification

Model	FM104SV001	
Screen Size	10.4" diagonal	
Active Area (H x V)	212.2 x 158.4 mm	
Resolution	800 x 600	
Aspect Ratio	4:3	
Color	16.2 Millions	
Viewing Angle	80° / 80° / 60° / 70°	
Luminance	400 cd/m ² (Standard Model) / 500~900 cd/m ² (High Brightness Model)	
Contrast	700:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
Power Input	12V DC	
Power Consumption	20 Watt	
Backlight Type & Life	LED & 70,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	Front Mounting	
	Back Mounting, VESA Mount (Optional)	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding



HIGHNESS MICROELECTRONICS PVT. LTD.

📍 101-103, Elecon Chambers, Sakinaka MTNL Road, Andheri (E), Mumbai - 400 072. India.

☎ +91 22 2850 7123 | 📠 +91 22 4026 4263

🌐 www.highnessmicro.com | ✉ sales@highnessmicro.com



An ISO 9001:2015 Company. Copyright @ 2019 Highness Microelectronics Pvt. Ltd. All Rights Reserved.

All images are for representation purpose only. All images and content are copyrighted & copy, reprint or reproduction without written permission prohibited.