

21.5" OPEN FRAME DISPLAY

FM215FH001



Model Numbers / Ordering Information

Model No.	Particulars	Details
FM215FH001	Base Model	-
FM215FH001-XX	Brightness	High Brightness
FM215FH001-XX-A	Input Interface	HDMI
FM215FH001-XX-B		HDMI, DVI & VGA Input
FM215FH001-XX-y-PT	Touch Screens	Projected Capacitive
FM215FH001-XX-y-RT		4 Wire Resistive Analog
FM215FH001-XX-y-5RT		5 Wire Resistive Analog
FM215FH001-XX-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
FM215FH001-XX-y-zz-HF		Surface Hardness Coating
FM215FH001-XX-y-zz-OB		Optical Bonding



Technical Specification

Model	FM215FH001	
Screen Size	21.5" diagonal	
Active Area (H x V)	476.64 x 268.11 mm	
Resolution	1920 x 1080	
Aspect Ratio	16:9	
Color	16.7 Millions	
Viewing Angle	89° / 89° / 89° / 89°	
Luminance	300 cd/m ² (Standard Model) / 500~900 cd/m ² (High Brightness Model)	
Contrast	3000:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
Power Input	AC 240V	
Power Consumption	45 Watt	
Backlight Type & Life	LED & 30,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	Front Mounting	
	Back Mounting, VESA Mount (Optional)	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding



HIGHNESS MICROELECTRONICS PVT. LTD.

📍 101-103, Elecon Chambers, Sakinaka MTNL Road, Andheri (E), Mumbai - 400 072. India.

☎ +91 22 2850 7123 | 📠 +91 22 4026 4263

🌐 www.highnessmicro.com | ✉ sales@highnessmicro.com



VOL M-L 1.0, June 2019

An ISO 9001:2015 Company. Copyright @ 2019 Highness Microelectronics Pvt. Ltd. All Rights Reserved.

All images are for representation purpose only. All images and content are copyrighted & copy, reprint or reproduction without written permission prohibited.