



Industrial Display Ruggedized Enclosure 7" Industrial Display ID070WX001-HB



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID070WX001-HB	Brightness	High Brightness
ID070WX001-HB-A	Input Interface	HDMI
ID070WX001-HB-B		HDMI, DVI & VGA Input
ID070WX001-HB-y-PT	Touch Screens	Projected Capacitive
ID070WX001-HB-y-4R		4 Wire Resistive Analog
ID070WX001-HB-y-5R		5 Wire Resistive Analog
ID070WX001-HB-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID070WX001-HB-y-zz-HF		Surface Hardness Coating
ID070WX001-HB-y-zz-OB		Optical Bonding



Industrial Automation

Technical Specification

Model	ID070WX001-HB	
Screen Size	7" diagonal	
Active Area	149.76 (H) x 93.6 (V) mm	
Resolution	1280 x RGB x 800 Dots	
Aspect Ratio	16:9	
Color	16.7 Million colors	
Viewing Angle	80° / 80° / 80° / 80° typical	
Luminance	1500 cd/m ² (Standard Model)	
Contrast	800:1 typical	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
Power Input	12V DC	
Power Consumption	20 Watt Approx	
Backlight Type & Life	LED & 50,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA standard	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

