



Industrial Display Ruggedized Enclosure 10.1" Industrial Display ID101WX001-HB



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID101WX001-HB	Brightness	High Brightness
ID101WX001-HB -A	Input Interface	HDMI
ID101WX001-HB -B		HDMI, DVI & VGA Input
ID101WX001-HB -y-PT	Touch Screens	Projected Capacitive
ID101WX001-HB -y-RT		4 Wire Resistive Analog
ID101WX001-HB -y-5RT		5 Wire Resistive Analog
ID101WX001-HB -y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID101WX001-HB -y-zz-HF		Surface Hardness Coating
ID101WX001-HB -y-zz-OB		Optical Bonding



Industrial Automation

Technical Specification

Model	ID101WX001-HB	
Screen Size	10.1" diagonal	
Active Area (H x V)	216.96 x 135.60 mm	
Resolution	1280 x 800	
Aspect Ratio	16:9	
Color	16.2 Millions	
Viewing Angle (H, V)	170°, 170°	
Luminance	500 cd/m ² (Standard Model) / 500~900 cd/m ² (High Brightness Model)	
Contrast	800:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
Power Input	12V DC	
Power Consumption	26 Watt	
Backlight Type & Life	LED & 50,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA Standard	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

