

Industrial Display Ruggedized Enclosure 20.1" Industrial Display ID201UX001



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID201UX001	Base Model	-
ID201UX001-xx	Brightness	High Brightness
ID201UX001-xx-A	Input Interface	HDMI
ID201UX001-xx-B		HDMI, DVI & VGA Input
ID201UX001-xx-C		DVI, HDMI, S-Video, Composite Video & VGA
ID201UX001-xx-y-PT	Touch Screens	Projected Capacitive
ID201UX001-xx-y-RT		4 Wire Resistive Analog
ID201UX001-xx-y-5RT		5 Wire Resistive Analog
ID201UX001-xx-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID201UX001-xx-y-zz-HF		Surface Hardness Coating
ID201UX001-xx-y-zz-OB		Optical Bonding



Technical Specification

Model	ID201UX001	
Screen Size	20.1" diagonal	
Active Area (H x V)	408.0 x 306.0 mm	
Resolution	1600 x 1200	
Aspect Ratio	4:3	
Color	16.7 Millions	
Viewing Angle (H, V)	178°, 178°	
Luminance	400~900 cd/m ²	
Contrast	800:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	AC 240V	
Power Consumption	60 Watt	
Backlight Type & Life	LED & 30,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA Standard / Wall Mount	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

