



Industrial Display Ruggedized Enclosure 32" Industrial Display ID320FH001-HB



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID320FH001-HB	Brightness	High Brightness
ID320FH001-HB-A	Input Interface	HDMI, DVI & VGA Input
ID320FH001-HB-B		DVI, HDMI, S-Video, Composite Video & VGA
ID320FH001-HB-y-PT	Touch Screens	Projected Capacitive
ID320FH001-HB-y-RT		4 Wire Resistive Analog
ID320FH001-HB-y-5RT		5 Wire Resistive Analog
ID320FH001-HB-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID320FH001-HB-y-zz-HF		Surface Hardness Coating
ID320FH001-HB-y-zz-OB		Optical Bonding



Industrial Automation

Technical Specification

Model	ID320FH001-HB	
Screen Size	32" diagonal	
Active Area (H x V)	698.4 x 392.85 mm	
Resolution	1920 x 1080	
Aspect Ratio	16:9	
Color	16.7 Millions	
Viewing Angle (H, V)	178°, 178°	
Luminance	500 cd/m ² (Standard Model) / 800~900 cd/m ² (High Brightness Model)	
Contrast	3000:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	AC 240V	
Power Consumption	34 Watt	
Backlight Type & Life	LED & 50,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA Standard / Wall Mount	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

