



Industrial Display Ruggedized Enclosure 43" Industrial Display ID430UH001



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID430UH001	Base Model	-
ID430UH001-PT	Touch Screens	Projected Capacitive
ID430UH001-xx-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID430UH001-xx-yy-HF		Surface Hardness Coating
ID430UH001-xx-yy-OB		Optical Bonding



Industrial Automation

Technical Specification

Model	ID430UH001
Screen Size	43" diagonal
Active Area (H x V)	941.184 x 529.416 mm
Resolution	3840 x 2160
Aspect Ratio	16:9
Color	1.07 Billions
Viewing Angle (H, V)	178°, 178°
Luminance	700 cd/m ²
Contrast	4000:1
Operating Temperature	-20° to +70° C
Storage Temperature	-20° to +70° C
Interface	HDMI, DVI & DP
Outputs Signals	DP
Power Input	AC 240V
Power Consumption	75 Watt
Backlight Type & Life	LED & 70,000 hours
Enclosure	Mild Steel / Aluminium
Mounting	VESA Standard / Wall Mount

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive
Interface	USB / I ² C / UART
Input Method	Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

