



Industrial Display Ruggedized Enclosure 65" Industrial Display ID650UH001-SHB



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID650UH001-SHB	Brightness	High Brightness
ID650UH001-SHB-A	Input Interface	DVI, HDMI, DP & VGA
ID650UH001-SHB-B		DVI, HDMI & DP
ID650UH001-SHB-C		VGA, HDMI, CVBS & DVI
ID650UH001-SHB-y-PT	Touch Screens	Projected Capacitive
ID650UH001-SHB-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID650UH001-SHB -y-zz-HF		Surface Hardness Coating
ID650UH001-SHB -y-zz-OB		Optical Bonding



Industrial Automation

Technical Specification

Model	ID650UH001-SHB	
Screen Size	65" diagonal	
Active Area (H x V)	1428.48 x 803.52 mm	
Resolution	3840 x 2160	
Aspect Ratio	16:9	
Color	1.07 Billions	
Viewing Angle (H, V)	178°, 178°	
Luminance	2000 cd/m ²	
Contrast	1200:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	DVI, HDMI, DP & VGA
		DVI, HDMI & DP
		VGA, HDMI, CVBS & DVI
Power Input	AC 240V	
Power Consumption	300 Watt	
Backlight Type & Life	LED & 50,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA Standard / Wall Mount	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive
Interface	USB / I ² C / UART
Input Method	Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

