

Industrial Display Ruggedized Enclosure 75" Industrial Display ID750UH001



Model Numbers / Ordering Information

Model No.	Particulars	Details
ID750UH001	Base Model	-
ID750UH001-xx	Brightness	High Brightness
ID750UH001-xx-A	Input Interface	DVI, HDMI, DP & VGA
ID750UH001-xx-B		DVI, HDMI & DP
ID750UH001-xx-C		VGA, HDMI, CVBS & DVI
ID750UH001-xx-y-PT	Touch Screens	Projected Capacitive
ID750UH001-xx-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
ID750UH001-xx-y-zz-HF		Surface Hardness Coating
ID750UH001-xx-y-zz-OB		Optical Bonding



RUGGED



MULTI TOUCH



HIGH BRIGHTNESS



Wall Mounting



4K ULTRA HD

Technical Specification

Model	ID750UH001	
Screen Size	75" diagonal	
Active Area (H x V)	1649.664 x 927.936 mm	
Resolution	3840 x 2160	
Aspect Ratio	16:9	
Color	1.07 Billions	
Viewing Angle (H, V)	178°, 178°	
Luminance	410 cd/m ² (Standard Model) / 500~900 cd/m ² (High Brightness Model)	
Contrast	1200:1	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	DVI, HDMI, DP & VGA
		DVI, HDMI & DP
		VGA, HDMI, CVBS & DVI
Power Input	AC 240V	
Power Consumption	230 Watt	
Backlight Type & Life	LED & 30,000 hours	
Enclosure	Mild Steel / Aluminium	
Mounting	VESA Standard / Wall Mount	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive
Interface	USB / I ² C / UART
Input Method	Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

