

Embedded Display 10.4" Embedded Panel PC IDE104XG001



Model Numbers / Ordering Information

Model No.	Particulars	Details
IDE104XG001	Base Model	-
IDE104XG001-LN	Linux Base Model	With Linux OS
IDE104XG001-AD	Android Base Model	With Android OS
IDE104XG001-xx-PT	Touch Screens	Projected Capacitive Touch Screen
IDE104XG001-xx-RT		4 Wire Resistive Analog
IDE104XG001-xx-5RT		5 Wire Resistive Analog

Technical Specification

Model	IDE104XG001	
Display Type	Active matrix TFT LCD with LED backlight	
Screen Size	10.4" Diagonal	
Active Area (H x V)	210.4 x 157.8 mm	
Aspect Ratio	4:3	
Resolution	1024 x 768	
Pixel Pitch (H x V)	0.0685 x 0.2055 mm	
Viewing Angle (H, V)	176°, 176°	
Luminance	500 cd/m ²	
Contrast Ratio	1200:1	
Color	16.2 Millions	
Response Time (Tr + Tf)	19 ms	
Built in System	Processor - Quad Core Cortex-A17, up to 1.8GHz RAM - 2GB DDR3 1600MHz (4GB Max) Built in 8GB Internal Storage (32 Max) I/O Port : USB2.0, I2C, GPIO, IR Comm. : Serial, UART TTL	
Operating System Support	Android	Lollipop, Marshmallow, Nougat & Oreo (Version)
	Linux	Linux (18.04) with kernel version 4.4.154
Supported Formats	Video Format	H.264, MPEG-4, MPEG-2, MPEG-1, H.263, AVI, MP4, DIV, TS, TP, TRP, MKV, MOV, DAT, ASF, WMV, RM, RMVB
	Image Format	JPEG, PNG
	Music Format	MP3, MP2, WMA, WAV
Network	Wi-Fi (up to 100 Mbps) Ethernet (100-1000 Mbps) Bluetooth	
Power Requirements	12V DC	
Operating Temperature	-10° to +60°C	
Storage Temperature	-20° to +70°C	
Power Consumption	26W Max	
Enclosure	MS Steel / Aluminum	
Mounting	VESA Standard	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive (Multi Touch) / 4/5 Wire Resistive
Interface	USB
Input Method	Stylus or Finger
Supported OS	Linux & Android

