

Industrial Display 20.1" Panel Mount PM201UX001



Model Numbers / Ordering Information

Model No.	Particulars	Details
PM201UX001	Standard	Standard Model
PM201UX001-A	Input Interface	HDMI
PM201UX001-B		HDMI, DVI & VGA Input
PM201UX001-C		DVI, HDMI, S-Video, Composite Video & VGA
PM201UX001-x-PT	Touch Screens	Projected Capacitive
PM201UX001-x-RT		4 Wire Resistive Analog
PM201UX001-x-5RT		5 Wire Resistive Analog
PM201UX001-x-yy-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
PM201UX001-x-yy-HF		Surface Hardness Coating
PM201UX001-x-yy-OB		Optical Bonding



Technical Specification

Model	PM201UX001	
Screen Size	20.1" diagonal	
Active Area (H x V)	432.0 x 331.5 mm	
Resolution	1600 x 1200	
Aspect Ratio	16:9	
Pixel Pitch (H x V)	0.255 x 0.255 mm	
Color	16.7 Millions	
Viewing Angle	89° / 89° / 89° / 89°	
Luminance	400 ~ 900 cd/m ²	
Contrast	800:1	
Response Time	25ms	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	AC 240V	
Power Consumption	69 Watt	
Backlight Type & Life	LED & 45,000 hours	
Handle	2x Industrial Grade Rugged Handle (Optional)	
Enclosure	Mild Steel / Aluminium	
Mounting	Front Mounting	
	Back Mounting, VESA Mount (Optional)	

Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I ² C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding

