

# Industrial Display 21.3" Panel Mount PM213UX001-HB



## Model Numbers / Ordering Information

Model No.	Particulars	Details
PM213UX001-HB	Brightness	High Brightness
PM213UX001-HB-A	Input Interface	HDMI
PM213UX001-HB-B		HDMI, DVI & VGA Input
PM213UX001-HB-C		DVI, HDMI, S-Video, Composite Video & VGA
PM213UX001-HB-y-PT	Touch Screens	Projected Capacitive
PM213UX001-HB-y-RT		4 Wire Resistive Analog
PM213UX001-HB-y-5RT		5 Wire Resistive Analog
PM213UX001-HB-y-zz-AG/AR/AF	Enhancements	Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
PM213UX001-HB-y-zz-HF		Surface Hardness Coating
PM213UX001-HB-y-zz-OB		Optical Bonding
PM213UX001-HB-y-zz-##-E		EMI-MESH



## Technical Specification

Model	PM213UX001-HB	
Screen Size	21.3" diagonal	
Active Area (H x V)	432.0 x 324.0 mm	
Resolution	1600 x 1200	
Aspect Ratio	4:3	
Pixel Pitch (H x V)	0.270 x 0.270 mm	
Color	16.7 Millions	
Viewing Angle	88° / 88° / 88° / 88°	
Luminance	900 cd/m <sup>2</sup>	
Contrast	1400:1	
Response Time	40ms	
Operating Temperature	-20° to +70° C	
Storage Temperature	-20° to +70° C	
Input Interface	Options	HDMI
		HDMI, DVI & VGA
		DVI, HDMI, S-Video, Composite Video & VGA
Power Input	AC 240V	
Power Consumption	75 Watt	
Backlight Type & Life	LED & 50,000 hours	
Handle	2x Industrial Grade Rugged Handle (Optional)	
Enclosure	Mild Steel / Aluminium	
Mounting	Front Mounting	
	Back Mounting, VESA Mount (Optional)	

## Touch Screens (Optional)

Touch Screen Type	Projected Capacitive / 4/5 Wire Resistive
Interface	USB / I <sup>2</sup> C / UART
Input Method	Finger / Stylus or Finger
Supported OS	Windows, Linux & Android

## Enhancement Solutions (Optional)

Anti-Reflective / Anti-Glare / Anti-Finger-Print Coating
Surface Hardness Coating
Optical Bonding
EMI-MESH

